


## Dimensions

Unit: Inch (mm)



## Summary

This NDAA-compliant MEGApiX® IP camera provides 2.1MP/1080p resolution at real-time 30fps, includes a 2.8-12mm vari-focal auto-focus lens with motorized zoom and simultaneous H.265/H.264/MJPEG codec support. The camera is powered by Star-Light Plus™ color in near-total darkness technology for quality video in any lighting conditions. The IP66-rated, IK-10 impact resistant vandal housing features CleanView™ self-cleaning dome treatment. All MEGApiX® cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

## Features

- 2.1MP/1080P sensor at real-time 30fps
- Star-Light Plus™ color in near-total darkness technology
- Vari-focal p-iris lens with motorized zoom and autofocus for complete remote lens control and focused image any time
- True Wide Dynamic Range (WDR) for clear images in challenging light
- Simultaneous streaming and multiple codec options for smart bandwidth management
- 100' Smart IR™ with intelligent camera sync for clear B/W images with no need for external light
- CleanView™ hydrophobic dome coating repels water, dust and grease.
- Smart DNR™ 3D digital noise reduction reduces noise and ghosting for motion in low-light environments.
- Privacy zones cover sensitive areas in the camera's field of view.
- Two-way audio for direct communication between the monitoring station and the camera's location
- Local SD card slot for local recording in case of network loss
- Alarm sensor input and relay output for access control integration
- Web server built-in for easy camera management from any browser
- PoE and DC12V for single cable simplified installation
- NDAA/TAA compliant for federal and government projects
- IP67- and IK10-rated camera housing built to last
- 5 year warranty



## Accessories (Optional)



DWC-V1CNMW  
Corner mount



DWC-VFCMW  
Ceiling mount bracket



DWC-VFJUNCW  
Junction box

DWC-VFWMW  
Wall mount bracket

## Specifications



<b>IMAGE</b>	
Image sensor	2.1MP/1080p 1/2.8" CMOS
Total pixels	1945 (H) X 1109 (V)
Minimum scene illumination	0.02 lux (color) 0.0 lux (B/W)
Video output	Local video output CVBS 1.0V p-p (75Ω), 16:9 aspect ratio
<b>LENS</b>	
Focal length	2.8-12mm, F1.4
Lens type	Vari-focal p-iris lens with motorized-zoom and auto-focus
HFOV / VFOF	96° - 35° / 51° - 20°
IR distance	100ft range
Optical zoom	x4.2 optical zoom
<b>I/O</b>	
Audio in/out and compression	1/1, G.711
Alarm in/out	1/1
<b>OPERATIONAL</b>	
Intelligent Video Analytics	IVA: intrusion, line crossing, counting line, loitering, enter, exit, tamper (DWC-MV82WiATW) IVA+: object removed, tailgating, direction, stopped, appear, disappear, object left, logical rules (DWC-MPV82WiATW)
Shutter mode	Auto, manual, anti-flicker, slow shutter
Shutter speed	1/15 - 1/32000
Slow shutter	1/2, 1/3, 1/5, 1/6, 1/7.5, 1/10
Auto gain control	Auto
Day and night	Auto, day (color), night (B/W)
3D digital noise reduction	Smart DNR™ 3D-DNR
Wide Dynamic Range (WDR)	True WDR, 120dB
Privacy zone	16 programmable privacy masks
Mirror and flip	Yes
Alarm notifications	Notifications via e-mail notifications, FTP, alarm output and SD card recording
Memory slot	Micro SD / SDHC / SDXC (card not included)
<b>NETWORK</b>	
LAN	10/100 Base-T
Video compression type	H.265, H.264, MJPEG
Resolution	H.265: 2.1MP/1080p, 720p, VGA, D1, CIF H.264: 2.1MP/1080p, 720p, VGA, D1, CIF MJPEG: 1280x720, 800x600, VGA, 768x432, D1, CIF
Frame rate	Up to 30fps at all resolutions
Video bitrate	100Kbps - 10Mbps, multi-rate for preview and recording
Bitrate control	Multi streaming CBR/VBR at H.264, H.265 (controllable frame rate and bandwidth)
Streaming capability	Dual-stream at different rates and resolutions
IP	IPv4, IPv6
Protocol	TCP/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2/v3 (MIB-2), ONVIF
Security	HTTPS (TLS), IP filtering, 802.1x, digest authentication (ID/PW)
ONVIF conformance	Yes
Web viewer	OS: Windows®, Mac® OS, Linux® Browser: IE®, Google Chrome®, Mozilla Firefox®, Safari® NOTE: Chrome browser is recommended for IVA configuration
Video management software	DW Spectrum® IPVMS
<b>ENVIRONMENTAL</b>	
Operating temperature	-4°F - 122°F (-20°C - 50°C)
Operating humidity	10-90% (non-condensing)
IP and IK rating	IP66-rated, IK10 impact-resistant
Other certifications	UL listed, CE, FCC, RoHS, NDAA, TAA
<b>ELECTRICAL</b>	
Power requirement	DC 12V, PoE IEEE 802.3af Class 3. (Adapter not included)
Power consumption	DC12V: max 6.5W, PoE: max 8.5W
<b>MECHANICAL</b>	
Material	Aluminum vandal housing, polycarbonate dome
Dimensions	4.9" x 3.6" (125 x 92 mm)
Weight	1.87 lb (0.85kg)
Warranty	5 year warranty



866.446.3595

sales@digital-watchdog.com



www.digital-watchdog.com

Built for Users.™

