


5MP turret IP camera DWC-MT95WiATW



unit: Inch (mm)



Specifications

Dimensions

IMAGE	
Image sensor	5MP 1/2.7" CMOS
Total pixels	2592 (H) x 1944 (V)
Total pixels	0.01 lux (color)
Minimum scene illumination	0.0 lux (B/W)
S/N ratio	50dB
LENS	1300D
Focal length	2.8 ~ 12mm, F1.4
Lens type	Vari-focal lens with motorized zoom and auto-focus
Field of view (FoV)	95.1°~ 30°
IR distance	164ft range
I/O	
Audio in / out	1 audio input and 1 microphone built-in
Audio compression	G.711A / U
OPERATIONAL	
Shutter mode	Auto, manual
Shutter speed	1/30s ~ 1/100000s
Auto gain control	Auto
Day / night	Auto, day (color), night (B/W), schedule
Smart DNR™ 3D digital noise reduction	
Wide dynamic range (WDR)	True WDR low, middle, high
Wide dynamic range (WDR) dB	120dB
Privacy zone	4 programmable privacy masks
0	Line crossing, perimeter intrusion, video tampering
Camera analytics	detection (scene change, video blur, abnormal
-	color detection), object classification (differentiate humans from objects)
Backlight compensation (BLC)	Yes
DeFog	Yes
Mirror and flip	Yes
Alarm notifications	Notifications via email or FTP server
	Micro SD / SDHC / SDXC card up to 256GB (card
Memory slot	not Included)
NETWORK	1
LAN	802.3 compliance 10/100 LAN
Video compression type	H.265, H.264, MJPEG
	5MP, 4MP, 2K, 3MP, 2.1MP/1080P, 720P (60Hz: 1 ~ 30fps; 50Hz: 1~25fps)
Resolution	HFR mode: 1080P / 720P
	(60Hz : 1 ~ 60fps; 50Hz: 1~50fps)
Frame rate	Up to 30fps at all resolutions
Video bitrate	64 Kbps ~ 8 Mbps
Bitrate control	Multi-streaming CBR/VBR at H.264/ H.265
	(controllable frame rate and bandwidth)
Streaming capability	Dual-stream at different rates and resolutions
IP	
Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, ICMP, IGMP, PPP0E, DDNS, SMTP, FTP, SNMP,HTTP, 802.1x,
	UPnP, HTTPs, QoS
Security	IP filtering, MAC filtering, authentication (ID/PW), SSL/TSL
ONVIF conformance	Yes
	OS: Windows*
Web viewer	Browser: Internet Explorer
Video management software	
	DW Spectrum [®] IPVMS
ENVIRONMENTAL	· · · · · · · · · · · · · · · · · · ·
	· · · · · · · · · · · · · · · · · · ·
ENVIRONMENTAL	DW Spectrum [®] IPVMS
ENVIRONMENTAL Operating temperature Operating humidity IP rating	DW Spectrum [®] IPVMS -22°F - 140°F (-30°C - 60°C)
ENVIRONMENTAL Operating temperature Operating humidity IP rating Other certifications	DW Spectrum® IPVMS -22°F - 140°F (-30°C - 60°C) 95% RH (non-condensing)
ENVIRONMENTAL Operating temperature Operating humidity IP rating	DW Spectrum [®] IPVMS -22°F - 140°F (-30°C - 60°C) 95% RH (non-condensing) IP67-rated FCC, CE, ROHS, POE, ONVIF
ENVIRONMENTAL Operating temperature Operating humidity IP rating Other certifications	DW Spectrum [®] IPVMS -22°F - 140°F (-30°C - 60°C) 95% RH (non-condensing) IP67-rated FCC, CE, ROHS, POE, ONVIF DC 12V, POE IEEE 802.3af Class 3.
ENVIRONMENTAL Operating temperature Operating humidity IP rating Other certifications ELECTRICAL Power requirement	DW Spectrum [®] IPVMS -22°F - 140°F (-30°C - 60°C) 95% RH (non-condensing) IP67-rated FCC, CE, ROHS, POE, ONVIF DC 12V, POE IEEE 802.3af Class 3. (Adapter not included)
ENVIRONMENTAL Operating temperature Operating humidity IP rating Other certifications ELECTRICAL Power requirement Power consumption	DW Spectrum [®] IPVMS -22°F - 140°F (-30°C - 60°C) 95% RH (non-condensing) IP67-rated FCC, CE, ROHS, POE, ONVIF DC 12V, POE IEEE 802.3af Class 3.
ENVIRONMENTAL Operating temperature Operating humidity IP rating Other certifications ELECTRICAL Power requirement Power consumption MECHANICAL	DW Spectrum [®] IPVMS -22°F - 140°F (-30°C - 60°C) 95% RH (non-condensing) IP67-rated FCC, CE, ROHS, POE, ONVIF DC 12V, POE IEEE 802.3af Class 3. (Adapter not included) 9W
ENVIRONMENTAL Operating temperature Operating humidity IP rating Other certifications ELECTRICAL Power requirement Power consumption	DW Spectrum [®] IPVMS -22°F - 140°F (-30°C - 60°C) 95% RH (non-condensing) IP67-rated FCC, CE, ROHS, POE, ONVIF DC 12V, POE IEEE 802.3af Class 3. (Adapter not included) 9W Metal turret housing
ENVIRONMENTAL Operating temperature Operating humidity IP rating Other certifications ELECTRICAL Power requirement Power consumption MECHANICAL Material	DW Spectrum [®] IPVMS -22°F - 140°F (-30°C - 60°C) 95% RH (non-condensing) IP67-rated FCC, CE, ROHS, POE, ONVIF DC 12V, POE IEEE 802.3af Class 3. (Adapter not included) 9W

Complete Surveillance Solutions"

Summary

These MEGApix® IP cameras are NDAA compliant and deliver crystalclear images at 5MP resolution and real-time 30fps. The IP67-rated turret camera features a 2.8-12mm vari-focal lens with motorized zoom and a 360° camera gimbal for absolute view adjustment. Added intelligence includes line crossing, perimeter intrusion, video tampering detection and object classification. All MEGApix cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

Features

- 5MP 1/2.7" image sensor at real-time 30fps
- 2.8~12mm vari-focal lens with motorized zoom and auto-focus
 True Wilds Durgenzia Dange (MVDD)
- True Wide Dynamic Range (WDR)
- Multiple codecs (H.265, H.264, MJPEG) with simultaneous dual-stream
- 164ft range Smart IR[™]
- Object classification video analytics
- Line crossing video analytics
- Perimeter intrusion video analytics
- Video tampering with scene change detection video analytics
- Video tampering with video blur detection video analytics
- Video tampering with abnormal color detection video analytics
- Smart DNR[™] 3D digital noise reduction
- True day/night with mechanical IR cut filter
- Programmable privacy zones
- Auto gain control (AGC)
- Backlight compensation (BLC)
- De-Fog[™] extreme weather image compensation
- Auto white balance (AWB)
- Motion detection
- Audio input through built-in microphone
- Micro SD/SDHC/SDXC class 10 card slot (card not included)
- Web server built-in
- PoE class 3 and DC12V
- ONVIF conformant, profile S
- NDAA compliant
- IP67 dust-tight and waterproof to 3 feet
- 5 year warranty



DWC-MTTWM2

Wall mount bracket

Mounting accessories (Optional)

DWC-MT9CMJ2 Ceiling mount bracket and junction box DWC-MT9JUNC2



